



**AMERICAN  
HAULER**

**HAULING THE AMERICAN SPIRIT**

# **PREMIUM RACE TRAILERS**

## **THE SILVER HAWK**



## **WIN BEFORE YOU TAKE THE GREEN**

We believe you will find our **SILVER HAWK** premium race trailers to be the best-built car haulers on the market today. Aside from its impressive list of standard equipment, the interiors and exteriors are engineered for safety, rugged durability, and great looks. Stop, Shop, and Compare. With an American Hauler® **SILVER HAWK** in tow, you're sure to be a winner before you even step foot on the track! And, as always, our trailers are made with pride in the USA!

*Trailers shown may feature optional equipment available at an additional charge.*

# SPECIFICATIONS

	SIL8520T3	SIL8524T3	SIL8528T4	SIL8532R4
<b>Body:</b> Length Width	20'0" 8'4"	24'0" 8'4"	28'0" 8'4"	32'0" 8'4"
<b>Overall:</b> Length Width Height (to top of roof vent)	24'7" 8'6" 9'1"	28'7" 8'6" 9'1"	32'7" 8'6" 9'3"	36'7" 8'6" 9'3"
<b>Interior:</b> Length Width Height	19'8" 8'1" 6'10"	23'8" 8'1" 6'10"	27'8" 8'1" 6'10"	31'8" 8'1" 6'10"
<b>Width Between Wheel Boxes</b>	83"	83"	83"	83"
<b>Height of Wheel Box from Floor</b>	10"	10"	10"	10"
<b>Platform Height at Beavertail</b>	19"	19"	21"	21"
<b>Torflex® Suspension E-Z Lube® Axles: Qty</b>	Tandem	Tandem	Tandem	Triple
<b>Electric Brakes with Breakaway Kit</b>	Electric Drum	Electric Drum	Electric Drum	Electric Drum
<b>Radial Tire Size Tire Load Range</b>	ST225/75R15 E	ST225/75R15 E	ST235/80R16 E	ST235/80R16 E
<b>Hitch Ball Size</b>	2-5/16"	2-5/16"	2-5/16"	2-5/16"
<b>Hitch Height to Top of Ball</b>	20"	20"	22"	22"
<b>Hitch Weight (% of Curb Weight)</b>	10% - 15%	10% - 15%	10% - 15%	10% - 15%
<b>GVWR</b>	9,900 lbs.	9,900 lbs.	12,000 lbs.	18,000 lbs.
<b>Rear Ramp Door Opening - Width x Height</b>	96" x 78"	96" x 78"	96" x 78"	96" x 78"
<b>12V Male Connection</b>	7-way	7-way	7-way	7-way
<b>Tube Main Rails</b>	2" x 6"	2" x 6"	2" x 8"	2" x 8"
<b>Beavertail</b>	48"	48"	72"	72"

## STANDARD FEATURES

- Flat Front/Flat Roof Design
- 16" OC Crossmembers, Wall Posts and Roof Structure
- 54" A-Frame with Center Tube
- 8,000 lb. Side Wind Drop Leg Jack
- .030 Aluminum Exterior, Smooth Bonded
- Cast Aluminum Corners (Front and Rear)
- Stainless Steel Cap and Front Corners
- Polished Aluminum Rear Corners & Header
- 1-Piece Aluminum Roof
- Armaguard on A-Frame and Rear End Rail
- 24" ATP Stoneguard
- Spring-Assist Rear Ramp Door with 94"W Opening
- 16" PlexCore Ramp Extension
- Locking Paddle Latches on Rear Ramp Door
- 36" x 78" Side Entry Door with Recessed Step
- Spread Torflex® Axles with Drop Skirting
- Radial Tires with Black Aluminum Wheels
- 12V Clear Lens LED Exterior Lighting
- 12V Clear Lens LED Slim Line Tail Lights (2 pair)
- 12V LED Dome Lights with Wall Switch
- Mid-Ship Amber Marker/Turn Light Combo
- 14" x 14" Non-Powered Roof Vents (2)
- 5,000 lb. Square D-Rings with Welded Plate (4)
- 3/4" PlexCore Decking
- 3/8" PlexCore Sidewall Liner
- Lauan Ceiling Liner
- Beavertail (48' to 72" depending on trailer length)
- 3-Year Limited Warranty



Silver Hawk images above shown with optional Turbo Package with Landing Strip In-Floor Lighting

