



**AMERICAN
HAULER**

HAULING THE AMERICAN SPIRIT

ALUMINUM STACKER TRAILERS



Trailers shown may feature optional equipment available at an additional charge.

TAKING THE SILVER HAWK TO NEW HEIGHTS

The American Hauler **SILVER HAWK STACKER** is for serious racers with multiple vehicles. Fully loaded out of the gate and nothing left to chance — featuring an aluminum frame design, Stinger® Lift, premium audio system, upper attic deck, finished interior including cabinets, and much more! You'll discover the **SILVER HAWK STACKER** is engineered for safety, rugged durability, and great looks. It's time to step up!

SPECIFICATIONS

	SIL8524TTA4-A-S	SIL8524TTA5-A-S	SIL8528TTA5-A-S	SIL8532TTA5-A-S
Body:				
Length	24' 0"	24' 0"	28' 0"	32' 0"
Width	8' 4"	8' 4"	8' 4"	8' 4"
Overall:				
Length	29' 0"	29' 0"	33' 0"	37' 0"
Width	8' 6"	8' 6"	8' 6"	8' 6"
Height	13' 5"	13' 5"	13' 5"	13' 5"
Interior:				
Length	23' 8"	23' 8"	27' 8"	31' 8"
Width	8' 0"	8' 0"	8' 0"	8' 0"
Height	11' 3"	11' 3"	11' 3"	11' 3"
Width Between Wheel Boxes	81"	81"	81"	81"
Platform Height	25"	25"	25"	25"
Auto Lift Length	13' 0"	13' 0"	16' 0"	16' 0"
Auto Lift Height	6' 8"	6' 8"	6' 8"	6' 8"
Torflex® Suspension E-Z Lube® Axles: Qty	Triple	Triple	Triple	Triple
Electric Brakes with Breakaway Kit	Electric Drum	Electric Drum	Electric Drum	Electric Drum
Radial Tire Size	ST235/85R16	ST235/85R16	ST235/85R16	ST235/85R16
Tire Load Range	E	E	E	E
Hitch Ball Size	2-5/16"	2-5/16"	2-5/16"	2-5/16"
Hitch Height to Top of Ball	23"	23"	23"	23"
Hitch Weight (% of Curb Weight)	10% - 15%	10% - 15%	10% - 15%	10% - 15%
GVWR	18,000 lb.	21,000 lb.	21,000 lb.	21,000 lb.
Curb Weight (Approximate)	7,600 lb.	8,750 lb.	9,600 lb.	10,700 lb.
Payload Capacity (Approximate)	10,400 lb.	12,250 lb.	11,400 lb.	10,300 lb.
Rear Ramp Door Opening - Width x Height	92" x 96"	92" x 96"	92" x 96"	92" x 96"
Side Double Door Opening - Width x Height	48" x 72"	48" x 72"	60" x 78"	60" x 78"
12v Male Connection	7-way	7-way	7-way	7-way
Tube Main Rails	2" x 8"	2" x 8"	2" x 8"	2" x 8"

STANDARD FEATURES

- Polished Aluminum Front Cap
- Stainless Steel Front Corners
- 1-Piece Aluminum Roof
- .040 Bonded Aluminum Exterior (Smooth Appearance)
- Spread Torflex Axles with Drop Skirting
- 24" ATP Stoneguard
- 8-Bolt 16" Goodyear Radial Tires with Black Aluminum Wheels
- 2⁵/₁₆" Adjustable Height Coupler w/ Steel Boot (25,000 lb.)
- 12K Single Leg Hydraulic Landing Gear
- 12v LED 24" 9K Lumen Scene Lights (4)
- 3/4" PlexCore™ Decking with Black Coin Rubber Floor Covering
- 3/8" PlexCore™ Sidewall Liner with .030 White Aluminum Covering
- White Aluminum Ceiling Liner
- Rear Ramp Door with Spring Assist
- 36" Aluminum Ramp Extension with Large Bumpers
- Premium Double Side Door with Pull-Out Step
- Cabinets: L-Shaped Base, Overhead and Generator Compartment (other configurations available at additional charge)
- Steel Car Hoist system with 36" Extension
- Upper Attic Deck (6' 6" from Floor)
 - >>Ladder Access only available on 28' & 32' models
- Generator Compartment with Access Door
- Air Compressor Prep Package — Hose, 4 Coupling and 120V Receptacle
- 120/240v 50 amp Motorbase Receptacle with Twist Lock Connect
- Battery Disconnect Switch
- 12v LED 36" Slim Line White Area/Accent Lights (8)
- 12v LED 6" Round Dome Lights (4)
- 16" OC Tube Crossmembers
- 16" OC Tube Vertical Posts
- 16" OC Tube Roof Structure
- D-Ring Tie-Downs with Welded Backer Plates (4)
- 3-Year Limited Warranty



Trailers shown may feature optional equipment available at an additional charge.

