



**AMERICAN  
HAULER**

**HAULING THE AMERICAN SPIRIT**

# **ENTRY-LEVEL TRAILERS**

## **THE ARROW**



## **A STRAIGHT SHOT TO A GREAT VALUE!**

The American Hauler **ARROW** is your path to dependable and low-maintenance cargo hauling that won't break the bank. It's a perfect fit for recreational and light-duty applications. Although classified as an "entry level" trailer, the ARROW is loaded with quality features found on much more expensive trailers. No matter your hauling needs . . . count on the **ARROW** to deliver your valuables safe and secure to your final destination.

# SPECIFICATIONS

	AR58SA	AR610SA2	AR612SA	AR714TA2	AR716TA2
<b>Body (L x W)</b>	9'5" x 5'0"	11'7" x 6'0"	13'7" x 6'0"	15'7" x 7'0"	17'7" x 7'0"
<b>Overall (L x W x H)</b>	11'6" x 6'8" x 7'2"	14'0" x 7'8" x 8'2"	16'0" x 7'8" x 8'2"	17'8" x 8'6" x 8'3"	19'8" x 8'6" x 8'3"
<b>Interior (L x W x H)</b>	9'1" x 4'8" x 5'6"	11'3" x 5'8" x 6'6"	13'3" x 5'8" x 6'6"	15'3" x 6'8" x 6'6"	17'3" x 6'8" x 6'6"
<b>Platform Height</b>	18"	18"	18"	19"	19"
<b>Side Door</b>	N/A	32" Bar Lock	32" Bar Lock	32" Bar Lock	32" Bar Lock
<b>Rear Door W x H</b>	Single Swing 51" x 59"	Ramp 63" x 72"	Ramp 63" x 72"	Ramp 75" x 72"	Ramp 75" x 72"
<b>Axle Quantity</b>	Single	Single	Single	Tandem	Tandem
<b>Brakes with Breakaway Kit</b>	N/A	Optional	Optional	Electric	Electric
<b>Radial Tire Size Tire Load Range</b>	ST205/75R15 C	ST205/75R15 C	ST205/75R15 C	ST205/75R15 C	ST205/75R15 C
<b>Hitch Ball Size</b>	2"	2"	2"	2-5/16"	2-5/16"
<b>Hitch Height to Top of Ball</b>	16"	16"	16"	17"	17"
<b>Hitch Weight (% of curb weight)</b>	10-15%	10-15%	10-15%	10-15%	10-15%
<b>Curb Weight (Approx.)</b>	935 lbs.	1,195 lbs.	1,325 lbs.	2,125 lbs.	2,275 lbs.
<b>GVWR</b>	2,990 lbs.	2,990 lbs.	2,990 lbs.	7,000 lbs.	7,000 lbs.
<b>Payload Capacity (Approx.)</b>	2,055 lbs.	1,795 lbs.	1,665 lbs.	4,875 lbs.	4,725 lbs.
<b>Main Rails</b>	2" x 3" Tube	2" x 3" Tube	2" x 3" Tube	2" x 4" Tube	2" x 4" Tube
<b>12v Connector</b>	4-Way	4-Way	4-Way	7-Way	7-Way

## STANDARD FEATURES

- Flat Roof with Tapered V-Nose Profile
  - 16" OC Vertical Posts
  - 24" OC Crossmembers
  - 24" OC Tube Roof Bows
  - Spring Axles with 4" Drop
  - E-Z Lube® Hubs
  - Electric Brakes with Breakaway Kit  
(Tandem Axle Models Only)
  - Chassis Undercoated
  - Ball Coupler Hitch
  - Safety Chains to D.O.T Standards
  - 15" Radial Tires with Silver Mod Wheels
  - Smooth Aluminum Radius Fenders
  - 1-Piece Seamless Aluminum Roof
  - .024 Aluminum Exterior with screws  
(White, Black or Pewter)
  - 16" Starbright Stoneguard
  - Flow-Thru Sidewall Vents
  - Rear Ramp Door with Spring Assist  
(Single Swing Door on 5'W Models)
  - 32" Side Door with Bar Lock (No Side Door on 5'W Models)
  - 12v LED Exterior Lighting & Slim Line Tail Lights
  - 12v LED Dome Light with self-switch
  - 3/4" PlexCore™ Interior Floor
  - Economy Sidewall Liner
  - 500 lb. Surface Mounted Wall Rope Rings (4)\*
  - 1-Year Limited Warranty
- Ask about our popular **DELUXE Package** with .030 Exterior, 3/8" PlexCore™ Sidewalls, Ramp Extension, and 5000 lb. Floor D-Rings.



5' x 8' Arrow with optional rear ramp door



7' x 16' Arrow with Deluxe Package

